

What is claimed is:

*Sub a1*  
1. An eye patch usable with eyeglass frames that comprises a bridge and a side arm, the eye patch comprising:  
a flexible body to be positioned on a front of the frames to substantially block both frontal and peripheral vision of an eye;  
a first fastener to attach the body to the bridge; and  
a second fastener to attach the body to the side arm.

*Sub B1*  
2. The eye patch of claim 1, wherein the eyeglass frames comprises a lens socket, and the body is adapted to at least partially extend over the lens socket.

*Sub C1*  
3. The eye patch of claim 1, wherein the eyeglass frames holds a lens, and the body is adapted to at least partially extend over the lens.

*Sub a1*  
4. The eye patch of claim 1, wherein the body is adapted to at least partially extend along the side arm.

*Sub a1*  
5. The eye patch of claim 1, wherein the first fastener comprises a loop comprising a first end secured to the body and a second end adapted to extend around the bridge to releasably couple the bridge to the body.

6. The eye patch of claim 5, wherein the first fastener further comprises: a releasable connector adapted to releasably couple the side arm to the body.

7. The eye patch of claim 5, wherein the body includes at least one slot, and the second end comprises a pronged tab adapted to be inserted into the slot to releasably couple the second end to the body.



1  
2  
3  
  
1  
2  
  
1  
2  
3  
  
1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25

17. The assembly of claim 16, wherein the eyeglass frames comprises a lens socket, and the body is adapted to at least partially extend over the lens socket.

18. The assembly of claim 16, wherein the body is adapted to at least partially extend along the side arm.

19. The assembly of claim 16, wherein the first fastener comprises a loop comprising a first end secured to the body and a second end adapted to extend around the bridge to releasably couple the bridge to the body.

20. The assembly of claim 19, wherein the first fastener further comprises: a releasable connector adapted to releasably couple the side arm to the body.

21. The assembly of claim 19, wherein the body includes at least one slot, and the second end comprises a pronged tab adapted to be inserted into the slot to releasably couple the second end to the body.

22. The assembly of claim 16, wherein the second fastener comprises at least one slot formed in the body to receive the side arm.

23. The assembly of claim 16, wherein the second fastener comprises: a loop adapted to extend around the side arm, the loop having a first end secured to the body and a second end.

24. The assembly of claim 23, wherein the second end is adapted to releasably couple the loop to the body.

25. The assembly of claim 23, wherein the second end is secured to the body.

1 26. The assembly of claim 16, wherein the body comprises a fabric selected from  
2 a set consisting essentially of: fabric and foam.

1 27. The assembly of claim 16, wherein the body comprises a fabric selected from  
2 a pliable material.

1 28. The assembly claim 16, wherein the first fastener is adapted to attach the body  
2 to the bridge regardless of whether the eye comprises a left eye or a right eye.

1 29. The assembly of claim 16, wherein the second fastener is adapted to attach the  
2 body to the side arm regardless of whether the eye comprises a left eye or a right eye.

30. An eye patch usable with eyeglass frames, comprising:  
a flexible body to be fastened to a front of the eyeglass frames to substantially block  
both frontal and peripheral vision of an eye; and  
at least one fastener to secure the flexible body to the frames.

Sub B27

31. The eye patch of claim 30, wherein  
the eyeglass frames comprises a lens socket, and  
the body is adapted to at least partially extend over the lens socket.

Sub a17

32. The eye patch of claim 30, wherein  
the body is adapted to at least partially extend along a side arm of the frames.

Sub B37

1 33. The eye patch of claim 30, wherein  
3 the eyeglass frames comprise a side arm and a bridge, and  
4 at least one fastener comprises:  
5 a first fastener to attach the eye patch to the bridge; and  
a second fastener to attach the eye patch to the side arm.

1  
2  
3  
4  
5  
6  
  
1  
2  
3  
  
1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100

34. An assembly comprising:  
eyeglass frames; and  
an eye patch comprising:  
a flexible body to be fastened to a front of the eyeglass frames to substantially  
block both frontal and peripheral vision of an eye; and  
at least one fastener to secure the flexible body to the frames.

35. The assembly of claim 34, wherein  
the eyeglass frames comprises a lens socket, and  
the body is adapted to at least partially extend over the lens socket.

36. The assembly of claim 34, wherein  
the eyeglass frames holds a lens, and  
the body is adapted to at least partially extend over the lens.

37. The assembly of claim 34, wherein  
the body is adapted to at least partially extend along a side arm of the frames.

38. The assembly of claim 34, wherein  
the eyeglass frames comprise a side arm and a bridge, and  
said at least one fastener comprises:  
a first fastener to attach the eye patch to the bridge; and  
a second fastener to attach the eye patch to the side arm.

*add  
a2*  
*Add B47*